



Dell UltraSharp U2719DC - LED monitor

27" (27" viewable) - 2560 x 1440 QHD @ 60 Hz - IPS - 350 cd/m² - 1000:1 - 5 ms - HDMI - DisplayPort - USB-C - with 3-Years Advanced Exchange Service and Premium Panel Guarantee

Group	Flat Screens
Manufacturer	Dell
Manufacturer item no.	210-AQYW
EAN/UPC	5397184092545
Additional	CNET accessory references

Description

Designed for performance. See fine details and true-to-life color on this 27" QHD monitor in an innovative, stylishly thin design with USB-C connectivity.

Main features

Product Description	Dell UltraSharp U2719DC - LED monitor - 27"
Device Type	LED-backlit LCD monitor - 27"
Energy Class	Class A
Energy Consumption per Year	40 kWh
Power Consumption (On mode)	27 W
Features	USB 3.0 hub
Panel Type	IPS
Aspect Ratio	16:9
Native Resolution	QHD 2560 x 1440 at 60 Hz
Pixel Pitch	0.233 mm
Brightness	350 cd/m ²
Contrast Ratio	1000:1
Response Time	8 ms (normal); 5 ms (fast)
Colour Support	16.7 million colours
Input Connectors	HDMI, DisplayPort, USB-C
Display Position Adjustments	Height, pivot (rotation), swivel, tilt
Screen Coating	Anti-glare, 3H Hard Coating
Dimensions (WxDxH) - with stand	61.22 cm x 18 cm x 39.02 cm
Environmental Standards	TCO Certified Displays 8, ENERGY STAR Qualified
Compliant Standards	RoHS, NFPA 99, DisplayPort 1.4, HDCP 1.4
Bundled Services	3-Years Advanced Exchange Service and Premium Panel Guarantee

Extended details

General	
Display Type	LED-backlit LCD monitor / TFT active matrix
Energy Class	Class A
Energy Consumption per Year	40 kWh
Power Consumption (On mode)	27 W
Diagonal Size	27"
Viewable Size	27"
Built-in Devices	USB 3.0 hub
Panel Type	IPS
Aspect Ratio	16:9
Native Resolution	QHD 2560 x 1440 at 60 Hz
Pixel Pitch	0.233 mm
Pixel Per Inch	109
Brightness	350 cd/m ²
Contrast Ratio	1000:1
Colour Support	16.7 million colours
Response Time	8 ms (normal); 5 ms (fast)
Horizontal Viewing Angle	178
Vertical Viewing Angle	178
Screen Coating	Anti-glare, 3H Hard Coating
Backlight Technology	LED backlight
Features	Daisy chain compatible, BFR/PVC-free, 99.9% sRGB colour gamut, Colour Calibration, arsenic-free glass, Dell Easy Arrange, 99% Rec 709 colour gamut, 85% DCI-P3
Dimensions (WxDxH)	61.22 cm x 18 cm x 39.02 cm - with stand
Connectivity	
Interfaces	DisplayPort † DisplayPort output (MST) † HDMI (HDCP) † 2 x USB 3.0 downstream † 2 x USB 3.0 downstream with Battery Charging 1.2 † USB-C † Audio line-out (mini-jack)
Mechanical	
Display Position Adjustments	Height, pivot (rotation), swivel, tilt
Tilt Angle	-5/+21
Swivel Angle	80
Height Adjustment	130 mm
VESA Mounting Interface	Yes
Miscellaneous	
Features	Security lock slot (cable lock sold separately), LED indicator, VESA interface support, anti-theft stand lock slot
Cables Included	1 x DisplayPort cable - DisplayPort to DisplayPort † 1 x USB-C cable - USB-C
Compliant Standards	RoHS, NFPA 99, DisplayPort 1.4, HDCP 1.4
Security Slot Type	Kensington security slot
Power	
Voltage Required	AC 120/230 V (50/60 Hz)

Power Consumption Operational	33.2 Watt
Power Consumption Stand by	0.3 Watt
Power Consumption Sleep	0.3 Watt
On / Off Switch	No
Software / System Requirements	
Included Software	Dell Display Manager
Dimensions & Weight	
Dimensions & Weight Details	With stand - width: 61.22 cm - depth: 18 cm - height: 39.02 cm Without stand - width: 61.22 cm - depth: 3.9 cm - height: 35.5 cm - weight: 4.19 kg
Dimensions & Weight (Shipping)	
Shipping Weight	8.72 kg
Environmental Standards	
TCO Certified	TCO Certified Displays 8
ENERGY STAR Certified	Yes
Manufacturer Warranty	
Bundled Services	3-Years Advanced Exchange Service and Premium Panel Guarantee
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	10 - 80% (non-condensing)

Technical data © CNET Content Solutions. Subject to technical modifications and errors.